

# **ACMG15 – 15.6" Room Booking Display Panel**

### **Product Information Data Sheet**

The Concierge 15.6" Display provides a snapshot of the room activity for the day.

It uses a simple green and red display to instantly notify whether the room is available or in use. There are side LEDs so the room availability can be seen from down the hallway.

# Friday, July 19, 2019 9:37 AM Meeting Room Available 11:00 PM — 2:30 PM 1:00 PM — 5:30 PM Private Meeting - Jane Tully 3:30 PM — 5:30 PM Private Meeting in the private Meeting in Jane Tully 1:00 PM — 2:00 PM Sales Meeting - John Smith Drivate Meeting in Jane Tully 1:00 PM — 2:00 PM Private Meeting in John Smith Private Meeting in John Smith

### **General Features**

- Hardened glass touch-screen
- 15.6" HD resolution (1920 x 1080)
- Side LED indicators
- Wi-Fi or Ethernet connectivity
- VESA compatible mounting options
- In-wall mounting option
- Window mounting option
- Multiple rooms on the one display
- Daily timeline view
- Supports Power over Ethernet (PoE)

- View daily, weekly or monthly booking information
- Book a room immediately
- Book a room for future date or time
- Extend or finish booking early
- Easily view room availability from a distance
- Easy to use web-based interface
- Room features displayed on screen (eg. projector, video conferencing)
- Report room features error through display (eg. projector malfunction)

### Compatibility

- Microsoft Exchange
- Office 365
- Google Apps
- Scienta Publish for Syllabus Plus
- Stand-alone mode
- Web-based configuration and monitoring directly on display or via Concierge Companion.

### **Specifications**

Display Size: - 15.6"

Resolution - 1910 x 1080

Viewing Angle H/V - 178 / 178 °

Brightness - 300 nits

Audio Speakers - 2 x 2w

General 10 point multi-touch

LED Side Bar x 2

**Physical I/O Connectors** 3.5mm TRS Stereo Audio



HDMI Out USB 2.0 x 2 RJ45 Ethernet DC Power In

Micro USB for ADB support

Power Requirements 12v DC 2A

802.3af compliance PoE

**Power Consumption** 14.15 watts max

**Environmental** Operating Temperature: 0-45 °C (32–113 °F)

Storage Humidity: 10-85% @ 40 °C (104 °F) non-condensing

**Mechanical** Dimensions: 402 mm x 253 mm x 30 mm (15.82" x 9.96" x 1.19")

Weight: 1320 g (2.917 lb)

Safety UL/CB certified AC adaptor

Certifications CE/FCC

Warranty One-Year parts and labour

## **Drawing**

