

# ACMG1000 – 10.1” NFC/RFID Room Booking Display Panel

## Product Information Data Sheet

The Concierge 10.1” NFC/RFID enabled Display provides a snapshot of the room activity for the day.

It uses a simple green and red display to instantly notify whether the room is available or in use. There is surround LED with wall projection so the room availability can be seen from down the hallway.



## General Features

- Hardened glass touch-screen
- 10” HD resolution (1280 x 800)
- Programmable surround with wall projection LED light
- Wi-Fi or Ethernet connectivity
- 75mm x 75mm VESA compatible mounting options
- In-wall mounting option
- Window mounting option
- Multiple rooms on the one display
- Daily timeline view
- Supports Power over Ethernet (PoE)
- View daily, weekly or monthly booking information
- Book a room immediately
- Book a room for future date or time
- Extend or finish booking early
- Easily view room availability from a distance
- Easy to use web-based interface
- Room features displayed on screen (eg. projector, video conferencing)
- Report room features error through display (eg. projector malfunction)

## Compatibility

- Microsoft Exchange
- Office 365
- Google Apps
- Scientia Syllabus Plus
- Celcat
- Stand-alone mode
- Web-based configuration and monitoring directly on display or via Concierge Companion.

## Specifications

<b>Display</b>	Size: - 10.1" LCD Panel Resolution - 1280 x 800 Viewing Angle H/V - 160° / 160° Brightness - 350 nits
<b>Audio</b>	Built-in 2w speaker
<b>General</b>	10 point Capacitive multi-touch Programmable surround LED with wall projection light
<b>Physical I/O Connectors</b>	3.5mm TRS Stereo Audio HDMI Out USB 2.0 x 2 RJ45 Ethernet DC Power In Micro USB for ADB support
<b>Power Requirements</b>	12v DC 2A 802.3af compliance PoE+
<b>Power Consumption</b>	14.15 watts max
<b>Environmental</b>	Operating Temperature: 0-40°C (32-104°F) Storage Humidity: 10-85% @ 40°C (104°F) non-condensing
<b>Mechanical</b>	Dimensions: 261mmW x 181mmH x 29mmD (10.28" x 7.12" x 1.14") Weight: 0.727Kg (1.6lbs)
<b>Safety</b>	UL/CB certified AC adaptor
<b>Certifications</b>	CE/FCC/RoHS
<b>Warranty</b>	One-Year parts and labour

## Drawing

